FAA APPROVED ROTORCRAFT FLIGHT MANUAL SUPPLEMENT

FOR THE SPECIFIC ROTORCRAFT FOUND WITHIN THE FAA APPROVED AML OF STC SR02617SE (S-70, UH-60, EH-60, HH-60) WHEN EQUIPPED WITH THE MECHANICAL SPECIALTIES MODEL 909 CARGO HOOK

REGISTRATION #: _____ SERIAL #: ____

The information in this supplement is FAA approved and must be attached to the appropriate Rotorcraft Flight Manual as per the FAA approved rotorcraft found within this STC's AML when the 909 Cargo Hook Kit is installed per
STC No. SR02617SE
The information contained in this document supplements or supersedes the basic manual only in those areas listed herein. For limitations, emergency procedures, normal procedures, and performance information not contained in this supplement, consult the basic FAA Approved Rotorcraft Flight Manual.
FAA APPROVED: For: Manager, Flight Test & Human Factors Branch, AIR-710 Federal Aviation Administration
FAA APPROVAL DATE: July 2, 2025

REVISION: 2

Mechanical Specialties, LLC

Rotorcraft Flight Manual Supplement

909-200 Cargo Hook Kit

Document No. MS-909-101-RFMS Revision 2

LOG OF REVISIONS

Rev	Date	Pg	Description	FAA Approval
IR		1-6	Original Release	Manager, Northwest Flight Test Section, AIR-715 Federal Aviation Administration Des Moines, Washington Date: 10/10/2018
1		i, ii, 1-6	Added EH-60, HH-60 series to title page & section 1	for Manager, Northwest Flight Test Section, AIR-715 Federal Aviation Administration Des Moines, Washington Date: 28 May 2020
2		i, 2, 3	Added "for the specific Type Certificate Data Sheets listed within the FAA approved AML"	for Manager, Flight Test & Human Factors Branch, AIR-710 Federal Aviation Administration Date: July 2, 2025

Mechanical Specialties, LLC

Rotorcraft Flight Manual Supplement

909-200 Cargo Hook Kit

Document No. MS-909-101-RFMS Revision 2

TABLE OF CONTENTS

SECTION		PAGE
SECTION I	GENERAL	2
SECTION II	LIMITATIONS	3
SECTION III	EMERGENCY PROCEDURES	3
SECTION IV	NORMAL PROCEDURES	5
SECTION V	PERFORMANCE	6
SECTION VI	WEIGHT & BALANCE	6

Mechanical Specialties ,
LLC

909-200 Cargo Hook Kit

Document No. MS-909-101-RFMS Revision 2

SECTION I GENERAL

This supplement is to be attached to the Rotorcraft Flight Manual of the respective rotorcraft listed within this STC's AML, when a Mechanical Specialties MODEL 909 Cargo Hook is installed.

The following information supplements or supersedes the existing rotorcraft flight manual only for the areas listed in this supplement. For limitations, procedures and performance data not contained in this supplement please consult the basic FAA approved Rotorcraft Flight Manual issued by Sikorsky Aircraft Corporation S-70, UH-60, EH-60, or HH-60 series Type Certificate Holders.

The Mechanical Specialties cargo hook MODEL 909 kit includes an electrical harness that interfaces with the rotorcraft's current electrical wiring and provisions for a manual cable release system as a backup.

FAA Approved Date: July 2, 2025

Page 2 of 6

Mechanical Specialties,
LLC

909-200 Cargo Hook Kit

Document No. MS-909-101-RFMS Revision 2

SECTION II LIMITATIONS

The basic Flight Manual issued by Sikorsky Aircraft Corporation S-70, UH-60, EH-60, and HH-60 series and other Type Certificate Holders listed within this STC's AML remain applicable. The Model 909 cargo hook has a limit load of 9000 lb., the limit load of the rotorcraft remains applicable, and may be less.

The external load equipment certification approval does <u>not</u> constitute operational approval: operational approval for external load operations must be granted by the local Aviation Authority.

The Model 909 cargo hook does not comply with 14 CFR part 29 certification requirements for Human External Cargo (HEC).

FAA Approved Date: July 2, 2025

Page 3 of 6

Mechanical Specialties	s,
LLC	

909-200 Cargo Hook Kit

Document No. MS-909-101-RFMS Revision 2

SECTION III EMERGENCY PROCEDURES

- The primary emergency load release procedure is the same as the normal load release procedure. Release of the cargo hook is done by pressing the CARGO REL switch on either cyclic stick grip or the CARGO HOOK NORMAL RLSE on the crewmember's cargo hook pendant.
- The secondary emergency load release procedure is done by pulling up the MANUAL RELEASE CABLE HANDLE located on the center console aft area, which can be accessed by either pilot.

WARNING

PRIMARY CARGO LOAD RELEASE WILL NOT FUNCTION IF NO. 1 DC PRI BUS IS SHED. IN THE EVENT OF SIGNIFICANT ROTOR DROOP OR OTHER ELECTRICAL LOAD SHED EVENT, EMERGENCY LOAD RELEASE WILL HAVE TO BE ACCOMPLISHED BY PULLING THE MANUAL RELEASE CABLE HANDLE.

FAA Approved Date: July 2, 2025

Page 4 of 6

Mechanical Specialties,
LLC

909-200 Cargo Hook Kit

Document No. MS-909-101-RFMS Revision 2

SECTION IV PREFLIGHT PROCEDURES

Prior to performing external load operations the following procedures shall be performed. If any of the following procedures are not successful do not use the equipment until the discrepancy has been resolved.

- 1. Visually check all mounting hardware to ensure security of the cargo hook.
- 2. Visually check the electrical harness and connection for damage and security.
- 3. Visually check the manual release cable and the connection to the cargo hook for damage and security.
- 4. Visually check the cargo hook for damage and hardware for security.
- Perform manual release using manual release handle on the center console aft area. Return load beam to locked position by manually pushing up on load beam.
- 6. Rotate cargo hook the full range of motion to insure there is no cable binding that can cause the cargo hook to open.
- 7. Place the **CARGO HOOK ARMING** switch to **ARMED**. A light on the advisory panel will go on, indicating **HOOK ARMED**.
- 8. Perform electrical release of cargo hook. Normal release of external cargo hook is done by pressing the **CARGO REL** switch on either cyclic stick grip or the **CARGO HOOK NORMAL RLSE** on the crewmember's cargo hook pendant. When the **CARGO REL** switch is pressed the load beam will swing open.

FAA Approved Date: July 2, 2025

Mechanical Specialties, LLC

Rotorcraft Flight Manual Supplement

Document No.
MS-909-101-RFMS
Revision 2

909-200 Cargo Hook Kit

NOTE

THE CARGO HOOK SHORT & TEST LAMP WILL NOT FUNCTION WHEN MODEL 909 CARGO HOOK IS INSTALLED.

WARNING

HOOK EMER REL ON COLLECTIVES & CREWMEMBER'S PENDANT ARE INOP WITH MODEL 909 CARGO HOOK INSTALLED.

Load Rigging

No Change

Operational Checks

No Change

Inflight

No Change

SECTION V PERFORMANCE

No change to basic Flight Manual.

SECTION VI WEIGHT & BALANCE

No change to basic Flight Manual.

FAA Approved Date: July 2, 2025

Page 6 of 6